

M E T R I C (公制)	螺紋尺寸 X螺距 Thread Size X Pitch	型號TYPE		螺紋碼 Thread Code	底端碼 Shank Code	A (Shank) Max.	最小板厚Min.S heetthickness(1)	安裝孔HoleSiz e inSheet+.08
		碳鋼Cabon Steel	不鏽鋼Stainles s Steel					
	M2*0.4	S	CLS	M2	0	0.77	0.8-1	4.25
					1	0.97	1	
					2	1.38	1.4	
	M2*0.45	S	CLS	M2.5	0	0.77	0.8-1	4.25
					1	0.97	1	
					2	1.38	1.4	
	M3*0.5	S	CLS	M3	0	1.38	0.8-1	4.25
					1	0.97	1	
					2	1.38	1.4	
	M3.5*0.6	S	CLS	M3.5	0	0.77	0.8-1	4.75
					1	0.97	1	
					2	1.38	1.4	
	M4*0.7	S	CLS	M4	0	0.77	0.8-1	5.4
					1	0.97	1	
					2	1.38	1.4	
	M5*0.8	S	CLS	M5	0	0.77	0.8-1	6.4
					1	0.97	1	
					2	1.38	1.4	
	M6*1	S	CLS	M6	0	1.15	1.2	8.75
					1	1.38	1.4	
					2	2.21	2.3	
	M8*1.25	S	CLS	M8	1	1.38	1.4	10.5
					2	2.21	2.3	
	M10*1.5	S	CLS	M10	1	2.21	2.31	14
					2	3.05	3.18	

C	Max.	E ±0.25	T ±0.25	最小邊距 Min.Dist.Hole C/LTo Edge
4.22		6.3	1.5	4.8
4.22		6.3	1.5	4.8
4.22		6.3	1.5	4.8
4.73		7.1	1.5	5.6
5.38		7.9	2	6.9
6.38		8.7	2	7.1
8.72		11.05	4.08	8.6
10.47		12.65	5.47	9.7
13.97		17.35	7.48	13.5